LIK40

Weatherproof IR camera with 3-Axis Bracket
IR LED: ∅5X42PCS, IR LED working distance: 40M
Water resistance: IP66 Cable built-in bracket
OSD Menu controlled by cable button (standard)
OSD Menu controlled by RS485 (optional)
Lens: CS Lens 6mm/F2.0
Dimension:228(W)x97(H)x82(D)mm ,Weight:1.4Kg

Model	LIK40SHE	LIK40SHR	LIK40SHD	LIK40HHD	LIK40SL
Image Sensor	1/3" SONY ICX673AK CCD	1/3" SONY ICX639BK CCD	1/3" SONY ICX639BK CCD	1/3" SHARP ICX639BK CCD	1/3" SONY ICX633BK CCD
Horizontal Resolution	700TV Lines Low Illumination, Effio, ATR, OSD, DNR	650TVL Low Illumination, DWDR, OSD, 3D DNR, Sense-up	600TV Lines Low Illumination, DWDR, OSD,DNR	600TV Lines Low Illumination	420TV Lines Low Illumination
Pixels	PAL:1020(H)×596(V), NTSC:1020(H)×508(V)	PAL:795(H)×596(V), NTSC:811(H)×508(V)	PAL:795(H)×596(V), NTSC:811(H)×508(V)	PAL:752(H)×582(V), NTSC:768(H)×494(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
TV System	PAL/NTSC				
Lens	CS Lens 6mm/F2.0				
Sync System	Internal				
Usable Illumination	0.001Lux/F2.0				0.0005Lux/F2.0
S/N Ratio	⩾65dB (AGC OFF)	⩾54dB (AGC OFF)			⩾48dB (AGC OFF)
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V500mA				
Dimension	228(W)x97(H)x82(D)mm				
Weight	1.4Kg				